

# Specification Statements FSH Products

## **1. High Security Electric Door Strike FES20M monitored**

"The electric door strike must be equal to the FSH FES20M model in all respects, be manufactured from stainless steel, accept voltages from 12 to 36VDC, pre-drilled for extension lips and be able to be site interchangeable, "power to lock" & "power to open" without removal of the body cover. The door strike should not contain any loose springs and pins.

The door strike must provide 3 forms of monitoring:

1. Internal locking mechanism (Lock Status Sensor)
2. Door latch/Lock tongue engaged within strike keeper (Door Status Sensor)
3. Anti-tamper monitoring (strike installed within door frame)

The door strike must be provided with a 5 year warranty and fire tested up to a 4 hour fire resistance rating to both Australian and British Fire Test Standards. The device has to be S.C.E.C. approved for Secure Areas and has to have a holding strength of up to 1490kg. The device also has to have a 10mm lip as well as a 5mm extension lip accessory as standard. "

### Product features

- 5 year warranty
- Simple power to lock/power to release interchange, no loose pins and springs
- Strike Lip 10mm, pre drilled for extension lips
- Mounting kit included
- Superior holding strength of up to 1490kg
- 4 hour fire rated
- Accepts 12 to 36vDC
- Fully monitored including "Anti-Tamper Monitoring" of the strike itself
- S.C.E.C. Approved for Secure Areas

## **2. High Security Electric Door Strike FES20 non-monitored**

"The electric door strike must be equal to the FSH model FES20 in all respects be manufactured from stainless steel, accept voltages from 12 to 36VDC, pre-drilled for extension lips and be able to be site interchangeable, "power to lock" & "power to open" without removal of the body cover. The door strike should not contain any loose springs and pins. It must be provided with a 5 year warranty and fire tested up to a

4 hour fire resistance rating to both Australian and British Fire Test Standards.

The device has to have a holding strength of up to 1490kg. The device also has to have an 10mm lip as well as a 5mm extension lip accessory as standard"

### Product features

- 5 year warranty
- Simple power to lock/power to release interchange, no loose pins and springs
- Strike Lip 10mm, pre drilled for extension lips
- Mounting kit included
- Superior holding strength of up to 1490kg
- 4 hour fire rated
- Accepts 12 to 36VDC